



Access Hatch for Roof Access 50 mm Thermally Broken SRHP50

Generated on 03.01.2018

Detailed description

Single leaf roof access hatch with a 50 mm thermal break and insulated with 0.43 W/m²K U-value polyisocyanurate insulation (non-combustible mineral wool also available). Manufactured from aluminium with a 300 mm kerb upstand.

Available with mill finish aluminium, or polyester powder coated.

Product guidance - As Standard

Material:

2 mm aluminium with 50 mm thermal break

Cover:

50 mm fully insulated kerb and lid, corner welded and reinforced.

Curb:

300 mm in height with external curb liner, 50 mm thermal break and 50mm insulation.

Seal:

Unbroken double seal to lid

Operation:

Gas spring assisted manual opening, designed to be opened smoothly and easily with secure stay hold-open arm.

Insulation:

- 50 mm HCFC and CFC free polyisocyanurate – U-value of 0.43 W/m²K.
- 50 mm Non-combustible Mineral Wool Insulation – U-value of 0.63 W/m²K.

Options

Fire rating:

Available up to 90 minutes. See SRH/TB-FR.

Acoustic Rating:

Available up to 45 dB available see SRH/TB-DB.

Product specification

Surespan Ltd



Surespan Ltd

Leamore Close

Leamore Enterprise Park

Walsall

West Midlands

WS2 7NL

Tel: +44 (0)1922 711185

www.surespancovers.com

sales@surespancovers.com



Manufacturer

- Name: Surespan Ltd
- Web: www.surespancovers.com
- Email: sales@surespancovers.com
- Tel: +44 (0)1922 711185
- Fax: +44 (0)1922 497943
- Address: Leamore Close, Leamore Enterprise Park, Walsall, West Midlands WS2 7NL

Product reference	SRHP50
Size	600 x 600 mm 750 x 750 mm 900 x 750 mm 900 x 900 mm 1000 x 1000 mm 750 x 1500 mm 1200 x 1200 mm 750 x 2500 mm 750 x 3300 mm
Material	Aluminium - Mill finish as standard. Stainless steel
Upstand	200 mm thermally broken and insulated 300 mm with a 50 mm thermal break and insulated - As standard. 385 mm thermally broken and insulated - Superior insulation only.
Colour/ Finish	
- Internal powder coating	Not required
- External powder coating	Not required
Insulation Options	50 mm Standard insulation (0.43 W/m ² K) - As standard. 50 mm Non-Combustible Mineral Wool (0.63 W/m ² K) 50 mm Superior Polyisocyanurate (0.20 W/m ² K) - Requires 385 mm upstand.
Operation	24 V electric motors Gas springs
Locking options	None L01 Cablock - As standard. L02 Cablock with hasp and staple L04 Cablock with external padlocking handle



L06 ABS Euro Cylinder with external key locking and thumb turn options
L07 European deadlock with internal and external key operation

Accessories

[None]

[Extended skirt liner] - Used in conjunction with retractable ZIP ladder.

[Fixed external handhold]

[Retractable Handhold] - Retracts into the opening of the roof hatch.

[Retractable ZIP ladder] - To suit Floor to ceiling height up to 3.5 m.

[SureGuard hand railing with self-closing gate] - Attached to the upstand of the hatch.