



Sliding Roof Hatch Fixed Rails

Generated on 03.01.2018

Detailed description

Surespan SLH sliding roof hatches and sliding glass rooflights are thermally broken and insulated. The sliding access hatch is ideal where there is a height restriction or in areas with high wind conditions.

Features double seals in addition to brush seals.

Product guidance - As Standard

Insulation:

50 mm HCFC and CFC free polyisocyanurate which offers a U-value of 0.43 W/m²K sandwiched in lid and upstand.

Upstand:

Thermally broken and insulated.

Loading:

Cover rated at a live load of 200 kg/m² when closed.

Warranty:

Ten-year manufacturer guarantee. Proprietary components will carry a one-year return to factory guarantee.

Product specification

Manufacturer

- Name: Surespan Ltd
- Web: www.surespancovers.com
- Email: sales@surespancovers.com
- Tel: +44 (0)1922 711185
- Fax: +44 (0)1922 497943
- Address: Leamore Close, Leamore Enterprise Park, Walsall, West Midlands WS2 7NL

Product reference TH.SLID/ F Fixed Rails

Type Aluminium solid top
Glazed rooflight

Size 750 x 2500 mm
750 x 3300 mm
1200 x 1800 mm

Surespan Ltd



Surespan Ltd

Leamore Close

Leamore Enterprise Park

Walsall

West Midlands

WS2 7NL

Tel: +44 (0)1922 711185

www.surespancovers.com
sales@surespancovers.com



1600 x 2400 mm
1800 x 750 mm
1800 x 2250 mm
1500 x 3000 mm
2400 x 3600 mm
3000 x 3000 mm

Material	Aluminium - Mill finish as standard. Stainless steel
Colour/ Finish	Not required Polyester powder coating - Any RAL colour, insert requirements.
Fire rating	Not required Required - Consult manufacturer and insert requirements.
Sound reduction	Not required Required - Consult manufacturer and insert requirements.
Operation	Manual sliding 24 V electric motors
Locks	Electric locking Internal shoot bolt with padlock hasp Spring loaded claw latch
Accessories	[None] [Extended skirt liner] [Retractable ZIP Ladder] [Shoot bolt]