



## Sliding Glass Rooflight

Generated on 03.01.2018

### Detailed description

Thermally broken sliding glass rooflight, incorporating double seals with a unique sealing feature which 'lifts off' the upstand on opening and re-seals on closing.

Telescopic sliding covers are ideal for smaller sizes that only require access for maintenance personnel or end-users. These are available in sizes of up to 750 x 2500 mm. Fixed sliding covers can be made to any size without limit; they are ideal for large equipment access as they provide the maximum clear opening.

### Features:

- Custom-made to any size.
- Fully insulated and energy-efficient.
- Internal telescopic rails available.
- Insulation U-value of 0.43 W/m<sup>2</sup>K.
- Mill-finish aluminium frame as standard; powder coating optional.
- Thermally broken lid and upstand.

### Product guidance - As Standard

#### Cover:

Thermally broken lid.

#### Insulation:

The lid is filled with 50 mm-thick CFC- and HCFC-free polyisocyanurate insulation, which offers a U-value of 0.43 W/m<sup>2</sup>K, a GWP (global warming potential) of 3 and an ODP (ozone depletion potential) of 0.

#### Upstand:

300 mm in height and manufactured in aluminium, with a 50-mm insulation thickness.

### Product specification

#### Manufacturer

- Name: Surespan Ltd
- Web: [www.surespancovers.com](http://www.surespancovers.com)
- Email: [sales@surespancovers.com](mailto:sales@surespancovers.com)
- Tel: +44 (0)1922 711185
- Fax: +44 (0)1922 497943

Surespan Ltd



**Surespan Ltd**

Leamore Close

Leamore Enterprise Park

Walsall

West Midlands

WS2 7NL

Tel: +44 (0)1922 711185

[www.surespancovers.com](http://www.surespancovers.com)

[sales@surespancovers.com](mailto:sales@surespancovers.com)



- Address: Leamore Close, Leamore Enterprise  
Park, Walsall, West Midlands WS2 7NL

<b>Product reference</b>	SLHP
<b>Size</b>	[ ]
<b>Rails</b>	Fixed Telescopic
<b>Material</b>	Aluminium Stainless steel
<b>Colour/ Finish</b>	
- Internal	Mill - Standard. Polyester powder-coated - Insert RAL colour requirement.
- External	Mill - Standard. Polyester powder-coated - Insert RAL colour requirement.
<b>Operation</b>	24 V electric motors Gas springs - Standard.
<b>Locking</b>	None DBH Lock, standard internal slam-action cablock - Deadlock with internal handles. EDH Deadlock, internally and externally key- opening Electrical locking
<b>Accessories</b>	[None] [Glazed top] [Rain skirt] [Retractable ZIP ladder] - To suit floor to ceiling height up to 3.5 m. [SureGrip non-slip finish] [SureGuard handrail] [Wind and rain sensors]