



Sliding Roof Hatch Telescopic

Generated on 03.01.2018

Detailed description

Sliding roof hatch and sliding glass rooflights which are thermally broken double sealed and insulated. The built in telescopic runners provide a means of travel without unnecessary external rails or supports. The sliding access hatch is ideal where there is a height restriction or in areas with high wind conditions. Features double seals in addition to brush seals.

Product guidance - As Standard

Material:

Aluminium - Mill finish as standard.

Insulation:

50 mm HCFC and CFC free polyisocyanurate which offers a U-value of 0.43 W/m²K sandwiched in lid and upstand.

Upstand:

Thermally broken and insulated.

Loading:

Cover rated at a live load of 200 kg/m² when closed.

Warranty:

Ten-year manufacturer guarantee. Proprietary components will carry a one-year return to factory guarantee.

Product specification

Manufacturer

- Name: Surespan Ltd
- Web: www.surespancovers.com
- Email: sales@surespancovers.com
- Tel: +44 (0)1922 711185
- Fax: +44 (0)1922 497943
- Address: Leamore Close, Leamore Enterprise Park, Walsall, West Midlands WS2 7NL

Product reference TH.SLID Telescopic Rails

Type Aluminium solid top - As standard.
Glazed rooflight

Surespan Ltd



Surespan Ltd
Leamore Close
Leamore Enterprise Park
Walsall
West Midlands
WS2 7NL

Tel: +44 (0)1922 711185

www.surespancovers.com
sales@surespancovers.com



Size	600 x 600 mm - As standard. 750 x 750 mm 750 x 1500 mm 900 x 750 mm 900 x 900 mm 1000 x 1000 mm 1200 x 1200 mm
Colour/ Finish	Not required Polyester powder coating - Any RAL colour, insert requirements.
Operation	Manual sliding 24 V electric motors
Locks	Electric locking Internal shoot bolt with padlock hasp Spring loaded claw latch
Accessories	[None] [Extended skirt liner] [Retractable ZIP Ladder] [Shoot bolt]