



Retrofit Conservation Roof Hatch

Generated on 03.01.2018

Detailed description

Thermally broken, low-profile roof hatch, manufactured in aluminium. Suitable for installation on landmark heritage buildings, the hatch is designed to provide a minimal sightline while still offering easy access. Designed to be operated by one person, the gas spring-assisted opening lid is supported by heavy-duty stainless steel hinges and fixings with a safety hold-open stay.

Available with mill-finish aluminium, or polyester powder-coated internally/externally in two colours to any standard RAL colour.

Product guidance - As Standard

Material:

Aluminium extrusions in 6063 -T6. Sheet aluminium, where used, is 1050 H14.

Cover:

The thermally broken lid incorporates a sandwich of 50 mm-thick CFC- and HCFC-free insulation. The hatch also incorporates a safety hold-open stay.

Upstand:

The hatch sits on a slim aluminium frame which sits over a builder's upstand. The unit has an overall height of 110 mm when closed.

Operation:

Complete with gas spring-assisted opening to ensure the minimum amount of effort to open the double-skinned aluminium lid. The lid has the provision to lock in the open position with a safety hold-open stay to prevent accidental closure.

Product specification

Manufacturer

- Name: Surespan Ltd
- Web: www.surespancovers.com
- Email: sales@surespancovers.com
- Tel: +44 (0)1922 711185
- Fax: +44 (0)1922 497943
- Address: Leamore Close, Leamore Enterprise Park, Walsall, West Midlands WS2 7NL

Surespan Ltd



Surespan Ltd

Leamore Close

Leamore Enterprise Park

Walsall

West Midlands

WS2 7NL

Tel: +44 (0)1922 711185

www.surespancovers.com

sales@surespancovers.com



| | |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product reference | SRH/RF |
| Size | 600 x 600 mm 600 x 900 mm 750 x 750 mm 750 x 1500 mm 900 x 750 mm 900 x 900 mm 1000 x 1000 mm 1200 x 1200 mm 1500 x 1000 mm - Maximum size available. Special order - Insert requirements, available up to 1500 x 1000 mm. |
| Colour/ Finish | |
| - Internal | Mill - Standard. Polyester powder-coated - Insert RAL colour requirement. |
| - External | Mill - Standard. Polyester powder-coated - Insert RAL colour requirement. |
| Insulation | 50 mm-thick premium insulation - 0.37 W/m ² K. 50 mm-thick standard insulation - 0.43 W/m ² K. 50 mm-thick superior insulation - 0.20 W/m ² K. |
| Locking | None L01 Cablock - Standard. L02 Cablock with hasp and staple L04 Cablock with external padlocking handle |