

ZIP RETRACTABLE LADDER ZIP 4-7



ZIP 4 - 7 RETRACTABLE LADDERS

Surespan's commercial heavy duty Zip ladders provide the simple solution to plant room access. Incorporating deep and wide anti-slip treads, a counterbalance spring action ensures that the stairway can be operated with a minimum of effort. Mounted on a headboard for easy installation. Maximum loading 200kg/tread or 500kg/m² of the overall structure.

Surespan Zip ladders are tested and certified to EN 14975.

MATERIALS

Die cast aluminium alloy and Aluminium non-slip treads.

OPERATION

Counter balanced springs are incorporated into the pivot bracket for easy opening.

HEAD BOARD

The timber headboard is 18mm thick 'block wood'. This should not be attached to the hatch

TREADS

Standard tread width is 350mm by 140mm depth. Alternate sizes between 200mm - 380mm (140mm depth) also available.

LOADING

200Kg per tread. 500kg/m² overall structure.

OPTIONS

Additional Grab rail
Additional steps

STANDARD SIZES

MODEL	HEADBOARD	MIN. APERTURE	DIMENSION 'X'	NO. OF TREADS	WEIGHT (KG)
ZIP 4	Up to 2500	600 x 900	1210 - 1310	9	28
ZIP 5	2501 - 2790	600 x 900	1310 - 1410	10	30
ZIP 6	2791 - 3090	600 x 900	1410 - 1510	11	32
ZIP 7	3091 - 3390	600 x 900	1510 - 1610	12	34

Note: Add 50mm to minimum aperture Width to allow frame thickness of Jakdor ceiling door. It is up to the customer to ensure the aperture size is large enough for their requirements.

