

## SURESPAN FLOOR DUCTING **FD**



### FD SPECIFICATION

**SURESPAN FD Floor Ducting to fit clear opening size 000 x 000, rated at FACTA Class 'A' pedestrian loading. With Tread Plate top. *Optional* Vinyl Floor infill. *Optional* 00mm Recessed Tray for infill.**

**Surespan Floor Ducting is manufactured from high grade aluminium sections with profiles specifically designed to incorporate a number of cost and time saving features over and above those of traditional curbing methods.**

### FAST & EASY TO INSTALL

the modular nature of system allows for pre-fabricated sections and corners to be made up.

### MOVEABLE ANCHOR POINTS

profile design allows the anchor lugs to be moved to any point along the length of the section accommodating inaccuracies in pre-cast pockets and easily allows the addition of extra lugs if required.

### COST EFFECTIVE

the flexibility of the system, together with its ease of installation drastically reduces time, against traditionally fabricated systems and eliminates fabrication errors and expensive mistakes on site.

### OPTIONAL FEATURES

Loading  
SUREGRIP Non-slip Coating  
Stainless Steel  
Fire Rating  
Acoustic to Rw45dB  
Watertight

### OPTION CODE

FACTA Class ?  
SGRIP  
SS304 or SS316  
FR60, FR120, FR180  
45dB  
WT

**DETAILS NEED TO BE INSERTED**  
REMOVE ANY OPTION IF NOT REQUIRED

